

## INJETORES SÉRIE "Q"

- ✓ Fabricados em PVC, PVDF, 316SS e Hastelloy C todos com Molas em Hastelloy C e Esferas em Cerâmica, fornecidas com ou sem Válvula de Bloqueio.



MODELO	Conexão (FNPT)	"L" Inserção (pol)	Material Corpo	Pres. Abertura (psig)	Pressão Máx. (barg)	Temp. Máx. (°C)
QP-.5-3	1/2"	3"	PVC	50	10	60
QP-.5-5	1/2"	5"	PVC	50	10	60
QP-.75-4	3/4"	4"	PVC	5	10	60
QP-.75-6	3/4"	6"	PVC	5	10	60
QP-1.0-5	1"	5"	PVC	5	10	60
QP-1.0-8	1"	8"	PVC	5	10	60
QK-.5-3	1/2"	3"	PVDF (Kynar)	50	10	137
QK-.5-5	1/2"	5"	PVDF (Kynar)	50	10	137
QK-.75-4	3/4"	4"	PVDF (Kynar)	5	10	137
QK-.75-6	3/4"	6"	PVDF (Kynar)	5	10	137
QK-1.0-5	1"	5"	PVDF (Kynar)	5	10	137
QK-1.0-8	1"	8"	PVDF (Kynar)	5	10	137
QS-.5-3	1/2"	3"	316/L SS	50	204	260
QS-.5-5	1/2"	5"	316/L SS	50	204	260
QS-.75-4	3/4"	4"	316/L SS	5	204	260
QS-.75-6	3/4"	6"	316/L SS	5	204	260
QS-1.0-5	1"	5"	316/L SS	5	204	260
QS-1.0-8	1"	8"	316/L SS	5	204	260
QH-.5-3	1/2"	3"	Hastelloy® C	50	204	260
QH-.5-5	1/2"	5"	Hastelloy® C	50	204	260
QH-.75-4	3/4"	4"	Hastelloy® C	5	204	260
QH-.75-6	3/4"	6"	Hastelloy® C	5	204	260
QH-1.0-5	1"	5"	Hastelloy® C	5	204	260
QH-1.0-8	1"	8"	Hastelloy® C	5	204	260

